NORTHROP GRUMMAN

NGSM VDR Service Bulletin No. 005-02 14<sup>th</sup> May 2013 Page 1 of 14

### Voyage Master VMII & VMIII - VDR APT Form

**SUBJECT:** Annual Performance Test (APT) – Addition of Manufacturer's Data Review

**INTRODUCTION:** Attached is the released Voyage Master VMII & VMIII

VDR Annual Performance Test Rev. 005

This bulletin supersedes the original VDR Bulletin No./APT Form:

APT\_VMIIIS-VMIII\_\_REVB APT\_VMIIS-VMII\_\_REVA

**SCOPE**: This Bulletin is to inform all personnel certified to perform the Voyage Master

II & III VDR Annual Performance Test of the revised Performance Test.

**GENERAL:** This Bulletin adds additional data review procedures to the APT to achieve

compliance with IMO MSC.1 Circ.1222 dated Dec 11, 2006, Issue 10. To

comply, conduct the APT, completing pages 3 of 14.

Sign the report, but do not issue the certificate.

**REQUIRED ACTION:** Approved service representatives and agents conducting APT's must while

on the vessel:

Download 12 hours of data from the capsule.

- Complete the Annual Performance Test (APT) form.
- Leave a copy of completed APT form with the vessel.

On completing the APT, the service representative or agent must then upload:

- 12 hours of data from the Capsule.
- A copy of completed APT form
- A copy of the service report
- A copy of valid training certificate.
- Sperry Service Order number or Purchase Order number for the issue of the COC.

Please use "NGSM\_VDR\_SB003 APT DATA UPLOAD" as guidance.

Once data analysis is complete, the completed report will be returned to the service representative.

Service representative have to send original certificate to vessel.

Northrop Grumman Sperry Marine B.V.

NORTHROP GRUMMAN

NGSM VDR Service Bulletin No. 005-02 14<sup>th</sup> May 2013 Page 2 of 14

#### ACTION:

Service Representatives must submit a Purchase Order to Sperry Marine with submittal of 12 hour data recording, incomplete report and incomplete certificate.

PO, incomplete report and incomplete certificate can be emailed to

vdr.apt@sperry.ngc.com.

#### Approved:



Global Product Support Supervisor Sperry Marine



Global Product Support & Training Manager Sperry Marine

NORTHROP GRUMMAN

NGSM VDR Service Bulletin No. 005-02 14<sup>th</sup> May 2013 Page 3 of 14

Service Report Number: 0158

Job Reference (optional): 510515

Name of Vessel	Flag	Class	IMO number	MMSI number
EL FARO	US	ABS	7395351	368208000

Vessel Type	
Passager Ship	
Cargo Ship	<b>✓</b>

#### Voyage Data Recorder information:

#### System Version:

Sperry Marine VDR II	
Sperry Marine VDR III	
Sperry Marine SVDR II	<b>✓</b>
Sperry Marine SVDR III	

Model No:	DAU S/No:	SW version installed at arrival:	Installation date: (dd.mm.yyyy)
GII	1000603	2.21	2003

#### Inspection details:

Certified Technician	Certificate number	Expiration date	Company name	Date of inspection	Location
		29 OCT 2016	SPERRY	2 DEC 2014	JACKSONVILLE, USA

### The following tools and test equipment must be available prior to this inspection:

Equipment	YES	NO	N/A
Laptop	✓		
Voltmeter	✓		
Test Kit P/N:1300652	✓		
Beacon Tester	✓		
PC Monitor			1

Check for existing alarms:	YES	NO
Are there any alarms presented in the system (Checked at the BAU)?		✓

Northrop Grumman Sperry Marine B.V.

NORTHROP GRUMMAN

NGSM VDR Service Bulletin No. 005-02 14<sup>th</sup> May 2013 Page 4 of 14

Check for saved incidents:		YES	NO
Check Bridge Alarm Unit for indication of saved incidents.			
Does BAU show "3 incidents left"?		✓	
If there is saved incidents in the system, transfer all these incidents to	a removable me	edia, an	d pass th
data to owner or Captain of the vessel. Do not at this time reinitialize	e the drives.		
Source of Energy:		YES	NO
	AC: 100 to 240 \		
Check main source of provided Energy is available	AC: 100 to 240 \ DC: 20 to 32 VD		ou.HZ
in accordance with requirements and specifications:	DC. 20 to 32 VD		
	AC:		
(Voyage Master II S-VDR o		<u>√</u>	<b>✓</b>
For a VDR where DC is not connected, confirm that the AC supply to t			<u> </u>
backed up by the vessels AC emergency power (automatic switch-ove		✓	
Internal Batteries expire at:	(mm.yyyy)	JAN 201	l R
If batteries are expired or will expire before the next Annual Perform			
will need to be replaced and fully charged before below power capa			itteries
will fleed to be replaced and fully charged before below power capa	icity test is perio	illeu.	
Check of Internal reserve power capacity:		YES	NO
Disconnect all AC power and DC power (if fitted) to S-VDR or VDR.		✓	Ш
Confirm that Bridge Alarm Unit is indicating this situation, by alarm co	ode.		
Check there is sufficient capacity to operate the basic equipment for 2	2 hours.		
At the end of this 2-hour period all recording shall cease automatical	У		
Confirm that S-VDR or VDR is still operational 1 hour and 55 minutes a	after power	✓	
removal.			Ш_
Confirm that S-VDR or VDR has switched off at 2 hours and 5 minutes	, after power	✓	
removal.			
Connect AC power and DC power (if fitted), and restart system.			
Check that Battery LED is flashing every second.		✓	
Overall condition of Equipment: Bridge Alarm Unit:		YES	NO
Confirm that Bridge Alarm Unit (BAU) display is adequately illuminate	ed.	✓	
Bridge Alarm Unit (BAU) is mounted at:			
Verify the DIM control can adjust the intensity of the background ligh	t	✓	
Perform BAU test by pressing ACK. Button for 5 seconds			
Did the BAU complete test successfully?	<u> </u>	✓	

Note the condition of the Bridge Alarm Unit (BAU): GOOD

Northrop Grumman Sperry Marine B.V.

NORTHROP GRUMMAN

NGSM VDR Service Bulletin No. 005-02 14<sup>th</sup> May 2013 Page 5 of 14

Visual inspect the Data Acquisition Unit for defects  Verify cabinet grounding to ship's hull  Verify tension of the grounding brackets for all signal cables  Verify Radar Video cable(s) are in good condition and well connected  Verify Microphone cables are in good condition and well connected  Verify VHF audio cable(s) are in good condition and well connected  Verify Serial cable(s) are in good condition and well connected  Verify Capsule cable are in good condition and well connected  Verify tension of the grounding brackets for capsule cable  Verify Ethernet cable(s) are in good condition and well connected (if fitted)  Verify CD with replay software and related documentation is placed inside the main  Cabinet (use ECO10149 10 ad ref.)	Overall condition of equipment: Data Acquisition Unit (DAU)	YES	NO	N/A
Verify tension of the grounding brackets for all signal cables  Verify Radar Video cable(s) are in good condition and well connected  Verify Microphone cables are in good condition and well connected  Verify VHF audio cable(s) are in good condition and well connected  Verify Serial cable(s) are in good condition and well connected  Verify Capsule cable are in good condition and well connected  Verify tension of the grounding brackets for capsule cable  Verify Ethernet cable(s) are in good condition and well connected   Verify Ethernet cable(s) are in good condition and well connected (if fitted)  Verify CD with replay software and related documentation is placed inside the main	Visual inspect the Data Acquisition Unit for defects	<b>√</b>		
Verify Radar Video cable(s) are in good condition and well connected Image: Connected of the connected of	Verify cabinet grounding to ship's hull	<b>√</b>		
Verify Microphone cables are in good condition and well connected Image: Connected of the provided of the	Verify tension of the grounding brackets for all signal cables	<b>√</b>		
Verify VHF audio cable(s) are in good condition and well connected       Image: Connected of the provided of the provi	Verify Radar Video cable(s) are in good condition and well connected	<b>√</b>		
Verify Serial cable(s) are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule cable are in good condition and well connected (if fitted)       Image: Capsule	Verify Microphone cables are in good condition and well connected	<b>√</b>		
Verify Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well connected       Image: Capsule cable are in good condition and well cable are in good cable a	Verify VHF audio cable(s) are in good condition and well connected	<b>√</b>		
Verify tension of the grounding brackets for capsule cable       Image: Capsule cable in good condition and well connected (if fitted)       Image: Capsule cable in good condition and well connected (if fitted)         Verify CD with replay software and related documentation is placed inside the main       Image: Capsule cable in good condition and well connected (if fitted)	Verify Serial cable(s) are in good condition and well connected	<b>√</b>		
Verify Ethernet cable(s) are in good condition and well connected (if fitted)       ✓       ✓       ✓         Verify CD with replay software and related documentation is placed inside the main       ✓       ✓       ✓	Verify Capsule cable are in good condition and well connected	<b>√</b>		
Verify CD with replay software and related documentation is placed inside the main	Verify tension of the grounding brackets for capsule cable	<b>√</b>		
	Verify Ethernet cable(s) are in good condition and well connected (if fitted)	✓		
cabinet (use ECO10149 10 ad ref.)	Verify CD with replay software and related documentation is placed inside the main	<b>√</b>		
Cabinet (use ECO10145-10 au lei.)	cabinet (use ECO10149-10 ad ref.)			

Note the condition of the Data Acquisition Unit (DAU): GOOD

#### Overall condition of equipment: Sensor Interface Unit (SIU) (only applies to VDR installations)

	YES	NO	N/A
Visual inspect the Sensor Interface Unit for defects			✓
Verify cabinet grounding to ship's hull			✓
Verify tension of the grounding brackets for all signal cables			✓
Verify Digital cable(s) are in good condition and well connected			✓
Verify Analog cable(s) are in good condition and well connected			✓
Verify Serial cable(s) are in good condition and well connected			✓
Verify Ethernet cable(s) are in good condition and well connected			✓

Note the condition of the Sensor Interface Unit: NA

### Overall condition of equipment: Remote Video Interface (RVI – if fitted)

		YES	NO	N/A
Visual inspect the Remote Video Interface for defects				
Verify cabinet grounding to ship's hull				
Verify Radar Video cables are in good condition and well conne	ected			
Verify Ethernet cable(s) are in good condition and well connec	ted			

Note the condition of the Remote Video Interface (RVI): NA

Northrop Grumman Sperry Marine B.V.

NORTHROP GRUMMAN

NGSM VDR Service Bulletin No. 005-02 14<sup>th</sup> May 2013 Page 6 of 14

#### Overall condition of equipment: NAS External Extended Memory (NAS - if fitted)

	YES	NO	N/A
Visual inspect the NAS External Extended Memory for defects			
Verify connection to power source			
Verify Ethernet cable are in good condition and connected correctly			

Note the condition o	the NAS External	Extended Memory: NA
----------------------	------------------	---------------------

#### Overall condition of Fixed Capsule:

#### Part Number / Serial Number:

1301603C4/A10631-000480

	YES	NO	N/A
Visual inspect the Fixed Capsule for defects	<b>√</b>		
Verify capsule cradle grounding to ship's hull	<b>V</b>		
Verify capsule is grounded by metal clamp. (only MK3 Capsules)	<b>√</b>		
Verify capsule cable is in good condition and installed correctly	<b>✓</b>		
Verify Fixed Capsule is highly visible and fully marked with reflective materials	<b>√</b>		
Verify Fixed capsule is mounted according to installation manual, and that an ROW can retrieve the Fixed Capsule when submerged.	<b>V</b>		
Verify the safety strips mounted and in good condition.	<b>√</b>		

Note the condition of the Fixed Capsule: GOOD

Acoustic Beacon: Battery and function test.

Maker/Model / Serial No:

TELEDYNE BENTHOS/TSOC121 ELP 362D/47368

	YES	NO
Check battery expiration date; has this date been reached?		1
If battery has expired or will expire before the next Annual Performance Test (APT),	the bea	con
will need to be replaced before COC can be issued.		

Date of expiry: (mm.yyyy) MAY 2015

If replaced, new battery expiry date: (mm.yyyy) \_\_\_\_\_

Northrop Grumman Sperry Marine B.V.

NORTHROP GRUMMAN

NGSM VDR Service Bulletin No. 005-02 14<sup>th</sup> May 2013 Page 7 of 14

#### Test of Beacon:

			YES NO	N/A
Is test showing a fully working	g Beacon.		✓ □	
Alternative:				
Test the beacon with the Ult	rasonic Tester and meas	uring battery voltage.	✓ □	
Voltage Measured			6\	/
Nete				
Note:				
Beacon Manufacture	Model		Minimum Volt	tage
Dukane	DK-120		2.9	97 V
Teledyne Benthos, Inc	ELP-362D		6.0	00 V
Where a sensor or external etest, please ensure that guide	equipment has been char	nged or repaired, since t	•	ance
			YES	NO
Have there been any change	S			
If you check the YES mark, pl	ease specify in below tak	ole, all the changes.		<b>√</b>
List of changes:				
Equipment	Change date	Software version	Other	
Equipment	Change date	Software version	Other	
Equipment	Change date	Software version	Other	

Northrop Grumman Sperry Marine B.V.



NORTHROP GRUMMAN

NGSM VDR Service Bulletin No. 005-02 14<sup>th</sup> May 2013 Page 8 of 14

Interfaces: Operation and recording:	Rec	orde	<u>k</u>	
Equipment	YES	NO	)	Notes
Microphone 1A	✓			
Microphone 1B	✓		]	
Microphone 2A	✓		]	
Microphone 2B	✓			
Microphone 3A	✓		]	
Microphone 3B				
Microphone 4 (AUD4)			]	
Microphone 5A			]	
Microphone 5B				
Microphone 5C				
Microphone 5D				
Primary VHF Audio	✓		]	FURUNO FM 8500
Specify source of data (e.g. SI01, DI02 or AN03) A	lways	inclu	de	an explanation or refer to one of the predefined
notes (see below table) when data listed below	is not	recor	de	d (except for optional video input and AIS).
Primary Radar Video <sup>2)</sup>	✓		<u>]                                    </u>	FURUNO
Optional Video Input 1			<u> </u>	
Optional Video Input 2			<u> </u>	
Optional Video Input 3			]	
AIS <sup>2)4)</sup>				
Date and Time (Master Clock in UTC)	✓		]	MX420
Ships position (Master position - GPS)	✓		]	MX420
Ships Speed (Master Speed - LOG)	✓		]	
Ships Heading (Master heading – Gyro)	✓		]_	NAVIGAT X
Water depth <sup>1)</sup>	✓			FURUNO FE700
Main Alarms <sup>1)</sup>			]	
Rudder order <sup>1)</sup>			]_	
Rudder response / actual <sup>1)</sup>			]_	
Status & settings of		▎┌	٦ .	
Heading or Track Controller (Autopilot) <sup>3)</sup>		<u> </u>	_	
Main Engine Order <sup>1)</sup>			<u> </u>	
Main Engine Response / Actual <sup>1)</sup>				
Thruster Order <sup>1)</sup>			]	
Thruster Response / Actual <sup>1)</sup>			]	
Hull Door Status <sup>1)</sup>			]	
Watertight Door and Fire Door Status <sup>1)</sup>		$\perp \Box$		
Acceleration and Hull Stress Data <sup>3)</sup>				
Wind Speed and Direction <sup>3)</sup>	✓			RM YOUNG
RNWΔS			7	

- 1) May be omitted for an S-VDR see 61996-2.
- 2) Radar may be substituted by AIS for an S-VDR see IEC 61996-2.
- 3) If suitable equipment is fitted.
- 4) A VDR is not required to record AIS data.

Above list are according IMO regulations. Predefined notes for exceptions which may be referred to from above table:

Note A: S-VDR - sensor data is not available in accordance with IEC61162

Note B: Substituted by AIS (S-VDR only)

Note C: Equipment not fitted on this vessel.

Note D: There is no status information displayed on the bridge related to this equipment in accordance with class approval.

Northrop Grumman Sperry Marine B.V.

NORTHROP GRUMMAN

NGSM VDR Service Bulletin No. 005-02 14<sup>th</sup> May 2013 Page 9 of 14

SOLA	AS MANDATORY ALARMS (Applicable for all ships) 1				
No.	IMO clause	Alarm	Notes	Alarm provided from which unit	Recorded bridge alarms
1	29.5.2 30.3	Main and auxiliary steering gear power units	Failure of power unit. Operation of devises for short circuit protection, overload, loss of phase in threephase system.		□Yes ✓ No
2	29.8.4	Main an auxiliary steering gear control system	Failure of power to control system.		☐Yes ✓ No
3	29.12.2	Steering gear, low hydraulic fluid level	Low level of fluid in hydraulic fluid reservoir.		☐Yes ✓ No
4	31.2.7 49.5	Propulsion machinery remote control system failure	For vessels with bridge control of propulsion machinery and manned engine room: failure of remote control of propulsion machinery.		☐Yes ✓ No
5	31.2.9 49.7	Propulsion machinery low starting air pressure	Vessels as 4 Low start air pressure but further starting of propulsion machinery possible.		☐ Yes ✓ No
6	15.7.3.1/ 25-9, 3 <sup>2</sup>	Watertight door low hydraulic fluid level	Passenger ships constructed on or after 1 February 1992 with hydraulic power operated sliding watertight doors. Low level of fluid in hydraulic reservoir.		☐ Yes ✓ No
7	15.7.3.1 <sup>2</sup>	Watertight door low gas pressure, loss of stored energy	Vessel as 9. Low gas pressure or loss of stored energy in operating hydraulic accumulator.		☐ Yes ☑ No
8	15.7.82	Watertight door electrical power loss	Vessels as 9. Failure of electrical power of operating or control system.		□Yes☑No

**Northrop Grumman Sperry Marine B.V.** 

NORTHROP GRUMMAN

NGSM VDR Service Bulletin No. 005-02 14<sup>th</sup> May 2013 Page 10 of 14

9	21.1.6.22	High water alarm	High water level in space where water has drained from enclosed cargo space or freeboard deck	☐ Yes ☑No
10	23-2.12	Shell door position indicator	Ro-Ro passenger vessels. Door open or locking device not secured. System to have mode switch for "sea or harbour". System active in "sea" mode	☐Yes ☑No
11	23-2.22	Water leakage detection indicator	Vessels as 13. Leakage of water through shell doors	☐ Yes ✓ No
12	5.3.4.33	Local automatic Halon release	Activation system to release Halon.	☐ Yes ✓ No
13	7,19 4	Fire detection or automatic sprinkler operation		☐ Yes ✓ No
14	A.830-3.8	Fire detection system power loss		☐Yes ✓No
15	5.3.3.83	Halon system loss of container	Decrease in pressure of gas in container.	□Yes ☑No
16	5.3.3.2³	Halon system electric circuit fault or loss of power	Failure of electric power to circuits connecting containers of gas release.	☐Yes ☑No
17	5.3.3.3³	Halon system- hydraulic or pneumatic pressure loss	Loss of pressure to pneumatic or hydraulic circuits for gas release.	□Yes ✓ No

<sup>1)</sup> For explanatory notes on the mandatory alarms in table, please see Annex B in IEC61996-1. Alarms separately identified for specialist vessels such as gas carriers, fishing vessels, nuclear ships, high speed craft or self propelled Mobile Offshore Drilling Units are in addition to this table. Self propelled MODUs to have VDR installed unless exempted by Flag Administration.

<sup>2)</sup> Applicable to vessels constructed on or after 1 February 1992.

<sup>3)</sup> These alarms may be omitted if provided at the central fire control station.

<sup>4)</sup> Where the fire detection system is of the addressable type that includes means of remotely identifying each detector individually, the activation of the individual detector should be recorded. Where the fire detection system identifies the detection of fire within a specified zone, the detection of fire within the individual zone should be recorded.

<sup>5)</sup> For installations of S-VDR the "No" box can be ticked if the alarm is not available in IEC 61162 format

NORTHROP GRUMMAN

NGSM VDR Service Bulletin No. 005-02 14<sup>th</sup> May 2013 Page 11 of 14

IMO R	Resolutions applica	ble for ships with periodic	ally unattended engine room E0.	
No	IMO clause	Alarm	Alarm provided from which unit	Recorded bridge alarms
1	52	Automatic shut down of propulsion machinery		□Yes☑No
2	51.1.3	Fault requiring action by or attention of the OOW		□Yes☑No
3	51.2.2	Alarm system normal power supply failure		☐Yes ✓ No
IMO R	Resolutions applica	ble for ship provided with	Personnel Alarm in the Engine Room.	
1	A.481(12) 7.3 A.830 (19) 7.1.1	Personnel alarm (dead man alarm)		☐Yes ✓ No
TANK July 2	002.		ction is only applicable for ships constructed ship type (NA for ships built before 1 July 20	
No	IMO clause	Alarm	Alarm provided from which unit	Recorded bridge alarms
1	4.5.10.1.3	Protection of cargo pump-rooms - Hydrocarbon gas alarm		☐Yes ☐ No
2	4.5.10.1.4	Protection of cargo pump rooms - High bilge level		□Yes□No
3	FSS 15.2.4.3	Inert gas system		☐Yes ☐ No
		ng alarms are applicable for		
ПАр	plicable to ship type	✓ Not applicable to ship ty	/pe	
No	IMO clause	Alarm	Alarm provided from which unit:	Recorded bridge alarms
1	MSC. 134(76) (SOLAS XII/12.2)	Water ingress pre-alarm		☐Yes ☐ No
2	MSC. 134(76) (SOLAS XII/12.2)	Water ingress main alarm		□Yes□No

NORTHROP GRUMMAN

NGSM VDR Service Bulletin No. 005-02 14<sup>th</sup> May 2013 Page 12 of 14

			des should be recorded when the alarms ar	re located on the
No	IMO clause	Alarm	Alarm provided from which unit	Recorded bridge alarms
1	IBC 15.2.4 BCH 4.19.4	High and low temperature of cargo and high temperature of heat exchanging medium (Ammonium nitrate solution 93% or less)		□Yes □ No
2	IBC 15.5.1.6 BCH 4.20.6	High temperature in tanks (Hydrogen peroxide solution over 60% but not over 70%)		☐ Yes ☐ No
3	IBC 15.5.1.7 BCH 4.20.7	Oxygen concentration in void spaces (Hydrogen peroxide solution over 60% but not over 70%)		□Yes□No
4	IGC 13.4.1 GC 13.4.1	High and low pressure in cargo tank		☐Yes ☐No
5	IGC 13.6.4, 17.9 GC 13.6.4,17.11	Gas detection equipment		□Yes□No
6	IGC 13.5.2, GC 13.5.2	Hull or insulation temperature		☐Yes ☐ No
7	IGC 17.18.4.4 GC 17.12.2(d)(iv)	Cargo high pressure, or high temperature at discharge of compressors (Methyl acetylene- propadiene mixtures)		□Yes□No
8	IGC 17.14.4.3	Gas detecting system monitoring chlorine concentration		□Yes □No
9	IGC 17.14.4.4	High pressure in chlorine cargo tank		☐Yes ☐No
10	IBC 15.5.2.5, BCH 4.20.19	High temperature in tanks (Hydrogen Peroxide solutions over 8% but not over 60% by weight)		☐Yes ☐No

Northrop Grumman Sperry Marine B.V.

NORTHROP GRUMMAN

NGSM VDR Service Bulletin No. 005-02 14<sup>th</sup> May 2013 Page 13 of 14

11	IBC 15.5.2.6, BCH 4.20.20	Oxygen concentration in void spaces (Hydrogen Peroxide solutions over 8% but not over 60% by weight)	☐Yes ☐ No
12	IBC 15.10.2, BCH 4.3. 1 (b)	Failure of mechanical ventilation of cargo tanks (Sulphur (molten))	□Yes □ No
13	IBC 19.8.4	Low pressure in inerted cargo tanks	□Yes□No
14	IGC 5.2.1.7, GC 5.2.5(b)	Liquid cargo in the ventilation system	☐Yes ☐ No
15	IGC 8.4.2. 1, GC 8.4.2(a)	Vacuum protection of cargo tanks	☐ Yes ☐ No
16	IGC 9.5.2, GC 9.5.2	Inert gas pressure monitoring	☐Yes ☐ No
17	IGC 13.6.1 1, GC 13.6.11	Gas detection equipment	☐ Yes ☐ No
18	IGC 17.14.1.4, GC 17.12.5(a) (iv)	Gas detection after bursting disk for chlorine	☐Yes ☐No

NORTHROP GRUMMAN

NGSM VDR Service Bulletin No. 005-02 14<sup>th</sup> May 2013 Page 14 of 14

This document is issued in respect of the regulations given by IMO, these can be seen on the Compliance Certificate. This document is also based on IMO guidance MSC.1/Circ.1222

Technicians Name (in print)	Technicians Signature
	Sperry Marine
Technicians Code/Certificate ID	Service Station / Company
see attached	2016
Service Station Class Certificate Number	Service Station Class Certificate Expiry Date
2 Dec 2014	Jacksonville, USA
Inspection date (dd.mm.yyyy)	Inspection location (City - Country)
Ships Representative Name (in print)	Ships Representative Signature
Service Technician Notes (Also use this for message	ges for the Manufacture):
Service Technician Notes (Also use this for message	ges for the Manufacture):
Service Technician Notes (Also use this for message	ges for the Manufacture):
Service Technician Notes (Also use this for message	ges for the Manufacture):
Service Technician Notes (Also use this for message	ges for the Manufacture):
Service Technician Notes (Also use this for message	ges for the Manufacture):
Service Technician Notes (Also use this for message	ges for the Manufacture):
Service Technician Notes (Also use this for message	ges for the Manufacture):
Service Technician Notes (Also use this for message	ges for the Manufacture):

Note: Discrepancies found will be advised to the vessel promptly. Sperry Marine's services will be offered if appropriate to correct faults. This service is not included in the performance test fee. All items will be corrected prior to issuing Certificate of Compliance. Any issues or questions of compliance will be addressed to Product Support Manager for guidance.

Northrop Grumman Sperry Marine B.V.

DATE OF

#### NORTHROP GRUMMAN

NGSM VDR Service Bulletin No. 002-02 14th May 2013 Page 6 of 6

### CERTIFICATE OF COMPLIANCE

Next Day Month Year TINSPECTION  Day Month Year TOYAGE DATA RECORDER (VDR)  VOYAGE DATA RECORDER (VDR)  ANNUAL PERFORMANCE TEST  NEW INSTALLATION PERFORMANCE TEST  Within 43 days. 10 accommodate performance checks to align with the appropriate survey under the Harmonized System of Survey and Certification (HSSC), the annual performance check may be carried out up to 3 months before the due date for a passenger ship and -/+ 3 months of the due date for a cargo ship. (The maximum period between subsequent checks is, therefore, 15 months for passenger ships and 18 months for cargo ships, unless either certificate has been extended as permitted by SOLAS regulation I/14, in which case a similar extension may be granted.)  MODEL: GII  DAU S/N: 1000603  CAPSULE S/N: a10631-000480  Service Report Number: US17486 0158	DATE OF	Day	y	Month		Ye	ear		MSC.1/Circ.			
Next   Day   Month   Year   No   No   North   Year   No   No   North   North   No   North   North	INSPECTION	0	2	1 2	2	0	1	4	within 45 day	s. To accommodate performance checks to align with the appropriate survey under		
INSPECTION    O   Z   D   D   D   D   D   D   D   D   D		Day		Month		**			be carried out	be carried out up to 3 months before the due date for a passenger ship and -/+ 3 months of the due		
VOYAGE DATA RECORDER (VDR)  ✓ SIMPLIFIED VOYAGE DATA RECORDER (S-VDR)  ANNUAL PERFORMANCE TEST  NEW INSTALLATION PERFORMANCE TEST  NEW INSTALLATION PERFORMANCE TEST  New Installation Performance Test  CAPSULE S/N: a10631-000480  Service Report Number: US17486 0158  IMO Number: 7 3 9 5 3 5 1 CLASS: ✓ABS DNV GL LR  Vessel Name: El Faro  Owner/MGR:  Service Supplier Class Certificate Number: Expiring Date: 16-Oct-2016  I hereby certify that on 02. December - 2014 , I conducted the Annual Performance Test on the VDR or S-VDR system described above and existing on the above wessel in accordance with SOLAS Chapter V Regulation Is 8 and found it to be in compliance with IMO Recommendation on Performance Standards for Simplified Voyage Data Recorders (VDR's) Resolution A.861 (20) or Performance Standards for Simplified Voyage Data Recorders (S-VDR's) MSCI63 (78) as applicable.  For your next inspection, please contact Service Control at:  Europe / Middle East: Phone - +13 (0) 10 44 15 1630 Service Cumber Vision Approved By Class:  Exceptions Approved By Class:  Exceptions Approved By Class:  Exceptions Approved By Class:  Phone - +16 (304) 371-3865 Service Use Septry Reg com North / South America: Phone - +65 272 3332						1 1		for pass		passenger ships and 18 months for cargo ships, unless either certificate has been extended as		
MANUAL PERFORMANCE TEST  NEW INSTALLATION PERFORMANCE TEST  NEW INSTALLATION PERFORMANCE TEST  NEW INSTALLATION PERFORMANCE TEST  To a service Report Number: US17486 0158  Service Report Number: US17486 0158  MANUAL PERFORMANCE TEST  CAPSULE S/N: a10631-000480  Service Report Number: US17486 0158  Expiring Date: 16-Oct-2016  Expiring Date: 16-Oct-2016  I hereby certify that on 02. December - 2014		0	2	1 2	2	0	1	4		, , , , , , , , , , , , , , , , , , ,		
MANUAL PERFORMANCE TEST  NEW INSTALLATION PERFORMANCE TEST  NEW INSTALLATION PERFORMANCE TEST  NEW INSTALLATION PERFORMANCE TEST  To a service Report Number: US17486 0158  Service Report Number: US17486 0158  MANUAL PERFORMANCE TEST  CAPSULE S/N: a10631-000480  Service Report Number: US17486 0158  Expiring Date: 16-Oct-2016  Expiring Date: 16-Oct-2016  I hereby certify that on 02. December - 2014										MODEL: GII		
ANNUAL PERFORMANCE TEST  OF NEW INSTALLATION PERFORMANCE TEST  OF NEW INSTALLATION PERFORMANCE TEST  OF Service Report Number: US17486 0158  IMO Number: 7 3 9 5 3 5 1 CLASS: ✓ABS _DNV _GL _LR	✓ SIMPLIFII	ED V	OYA	AGE DA	TAI	REC	ORD	ER (	S-VDR)	DAU S/N: 1000603		
NEW INSTALLATION PERFORMANCE TEST  Service Report Number: US17486 0158  IMO Number: 7 3 9 5 3 5 1 CLASS: ✓ABS _DNV _GL _LR	111000000000000000000000000000000000000									CAPSULE S/N+ a10631-000480		
IMO Number: 7 3 9 5 3 5 1 CLASS: ✓ABS _DNV _GL _LR				03"			NOT	s anese	Trans			
Vessel Name: El Faro  Owner/MGR:  Service Supplier Class Certificate Number:  Expiring Date: 16-Oct-2016  I hereby certify that on 02. December - 2014 , I conducted the Annual Performance Test on the VDR or S-VDR system described above and existing on the above vessel in accordance with SOLAS Chapter V Regulation 18.8 and found it to be in compliance with IMO Recommendation on Performance Standards for Voyage Data Recorders (VDR's) Resolution A.861 (20) or Performance Standards for Simplified Voyage Data Recorders (S-VDR's) MSC163 (78) as applicable.  Manufacturer Representative Name and Signature  For your next inspection, please contact Service Control at:  Europe / Middle East: Phone + 31 (0) 10 44 51 630  service eu/asperty ngc com North / South America: Phone + -1 (504) 371-8365 service us/asperty ngc com Asia: Phone - +65 272 3332	NEW INS	IALL	AH	ION PEI	(FOI	KMA	NCE	LIES	81	Service Report Number: US1/486 0158		
Vessel Name: El Faro  Owner/MGR:  Service Supplier Class Certificate Number:    Expiring Date: 16-Oct-2016	IMO Number:	7	3	9	5 3	3 5	5 1		CLASS: ✓	ABS DNV GL LR softers		
Service Supplier Class Certificate Number:    Expiring Date: 16-Oct-2016					-			_				
Service Supplier Class Certificate Number:    I hereby certify that on	Vessel Name: E	El Far	0									
Service Supplier Class Certificate Number:    I hereby certify that on	Owner/MGR:											
Thereby certify that on	owner/More.											
Thereby certify that on												
Manufacturer Representative Name and Signature  For your next inspection, please contact Service Control at:  Europe / Middle East: Phone - +31 (0) 10 44 51 630 service eu@sperry.ngc.com  North / South America: Phone - +1(504) 371-8365 service.us@sperry ngc.com  Asia: Phone - +65 272 3332	described about compliance with	ove an	nd e:	xisting o commen	n the datio	abov on on	ve ve Perj	ssel i forma	in accordance ance Standard	with SOLAS Chapter V Regulation 18.8 and found it to be in Is for Voyage Data Recorders (VDR's) Resolution A.861 (20) or		
Manufacturer Representative Name and Signature  For your next inspection, please contact Service Control at:  Europe / Middle East: Phone - +31 (0) 10 44 51 630 service eu@sperry.ngc.com  North / South America: Phone - +1(504) 371-8365 service.us@sperry ngc.com  Asia: Phone - +65 272 3332				Í								
For your next inspection, please contact Service Control at:  Europe / Middle East: Phone - +31 (0) 10 44 51 630 service eu@sperry.ngc.com  North / South America: Phone - +1(504) 371-8365 service.us@sperry.ngc.com  Asia: Phone - +65 272 3332							MOR			CHICH		
For your next inspection, please contact Service Control at:  Europe / Middle East: Phone - +31 (0) 10 44 51 630 service eu@sperry.ngc.com  North / South America: Phone - +1(504) 371-8365 service us@sperry ngc.com  Asia: Phone - +65 272 3332												
Europe / Middle East: Phone - +31 (0) 10 44 51 630 service.eu@sperry.ngc.com  North / South America: Phone - +1(504) 371-8365 service.us@sperry.ngc.com  Asia: Phone - +65 272 3332								Ze .	Exp: 20-Oct-201	6		
Europe / Middle East: Phone - +31 (0) 10 44 51 630 service.eu@sperry.ngc.com  North / South America: Phone - +1(504) 371-8365 service.us@sperry.ngc.com  Asia: Phone - +65 272 3332												
Phone - +31 (0) 10 44 51 630  service.eu@sperry.ngc.com  North / South America: Phone - +1(504) 371-8365 service.us@sperry.ngc.com  Asia: Phone - +65 272 3332					Ex	ceptio	ons A	Appro	oved By Class			
Phone - +31 (0) 10 44 51 630  service.eu@sperry.ngc.com  North / South America: Phone - +1(504) 371-8365 service.us@sperry.ngc.com  Asia: Phone - +65 272 3332	Europe / M	iddle	East	t:	=					0		
North / South America: Phone - +1(504) 371-8365 service.us/a/sperry.ngc.com  Asia: Phone - +65 272 3332	Phone - +31 (0	10 44	151	630						2		
Phone - +1(504) 371-8365 <u>service.us@sperry.ngc.com</u> Asia: Phone - +65 272 3332	service.eu/a/sp	erry n	gc.c	om								
Asia: Phone - +65 272 3332	North / Sout	h Am	eric	a:	-							
Asia: Phone - +65 272 3332												
Phone - +65 272 3332	service us(a)sp	erry n	gc.ce	2111	_		_			Þ		
	As	ia:			-							
service.asia@sperrv.ngc.com			2222									
	service asia(a)s				-							

Northrop Grumman Sperry Marine B.V. vdr.support@sperry.ngc.com vdr.apt@sperry.ngc.com service.eu@sperry.ngc.com